

HOST AdBlue SBT



HOST AdBlue Self Bunded Storage Tanks

The safest, simplest and smartest way to store and dispense AdBlue (DEF) solution.

Available in five industry preferred sizes (including a 10,000 L slimline) ranging from 3,000L to 20,000L, these insulated internal Stainless Steel Self Bunded AdBlue tanks are A-class. The insulation maintains a more consistently regulated temperature, avoiding premature expiry of the AdBlue solution, enabling it to remain at its highest quality. And like all HOST RTR supplied tanks, a variety of quality pump dispensing and Fuel Management Systems (FMS) can be custom fitted and commissioned, providing the ideal plug and play storage solution for your application.

Including high quality stainless steel fittings throughout and many other valuable features as standard, HOST AdBlue Self Bunded Tanks really stack up on design and value.



Insulated
Stainless Steel
Internal tank



HOST AdBlue Self Bunded Storage Tanks – features and pumping options

The HOST AdBlue range come in sizes ranging from 3,000 to 20,000 litres and are designed to AS1940 and built to AS1692. Tanks can be supplied fitted with any number of high quality pumping systems, meters and FMS.

STANDARD ADBLUE TANK FEATURES

- ▶ Tank outer shell, steel with Epoxy coating
- ▶ Stainless Steel inner tank
- ▶ Stainless Steel tank with Hatch, 2" port and 3" ports
- ▶ Insulated 40 mm space between the two tank walls
- ▶ Front door access, with heavy duty container locking bars standard
- ▶ Stainless Steel Piping – suction and fill lines
- ▶ Stainless Steel Drybreak – 2" adaptor fitted on fill line
- ▶ Stainless Steel Y-Strainer – 2" fitted on Suction line
- ▶ Stainless Steel Overfill Valve fitted in tank
- ▶ Stainless Steel Anti-syphon Valve fitted in tank
- ▶ Blasted to 2.5, primed and painted in 2 coat Marine Grade Epoxy 260 um minimum on exterior
- ▶ Grate mesh on floor in pump bay
- ▶ Manway on top to access internal Stainless Steel tank
- ▶ Lifting lugs for roof
- ▶ Forklift access points
- ▶ Pump bay side access panels for remote pipe connections
- ▶ Optional Level gauge and sump sensor

PUMP DISPENSING OPTIONS

- ▶ 240 V Mains Power with mechanical metre – up to 100 L/min
- ▶ Fuel Management System – with pump packages

CERTIFICATIONS

- ▶ Built to AS1692-2006 Steel tanks for Flammable & Combustible Liquids
- ▶ AS1940-2004 The storage and handling of Flammable & Combustible Liquids



HOST ADBLUE SBT RANGE -Tank sizes and models available through RTR

Tank Model	Safe Fill Capacity (Litres)	Tank Length (metres)	Tank Width (metres)	Tank Height (metres)	Empty Tank Weight (kg)	Dispensing options
T3	3,000	2.752	1.130	2.566	1800	Pump Bay
T5	5,400	4.053	1.140	2.550	2360	Pump Bay
T10	11,500	3.960	2.266	2.504	3205	Pump Bay
T10 Slimline	10,000	6.850	1.220	2.500	3710	Pump Bay
T20	20,000	6.960	2.250	2.500	5100	Pump Bay

11 Camomile Way,
Bibra Lake
W.A, 6163

Phone: (08) 6166 3860
E-mail: admin@rtrswa.com.au

