Piusi Cube 70MC Diesel Dispenser





Piusi Cube 70MC Diesel Dispenser

Diesel fuel dispenser for non commercial use

Sturdy structure designed for different applications: can be fixed to walls, tanks cisterns, drums, special pedestals. Self-priming vane pump fitted with bypass, installed on anti-vibration supports. Mechanical seal. Induction motor fitted with thermal motor overload protection.


Available in AC and 12-24V DC power options.

Dispenser includes:

- ▶ Automatic nozzle with swivel connection.
- ▶ Integrated nozzle holder with stop/start pump lever.
- Intake mesh filter.

Magnetic keys (Kit keys) available for user identification.

Requires a dedicated software for printing individual summaries of dispensing details.





Piusi Cube 70MC Diesel Dispenser

Optional Accessories

- Kit Wall Support
- Water Captor Filter
- Kit Lock
- DC Version wiring kit
- 2" Quick Coupling
- 2" Drum Connector

Features

Flow Rate

▶ Up to 70 l/min (18g/pm)

Accuracy

+/- 0.5%

Users

▶ 120 maximum users



25

25

55

55

		- 15	CATOR CITY ST ST SEED OF ST				
Product Specifications (weight & packaging)							
	Code	Weight		Packaging		No. Boxes / Europallet	
		kg	lbs	Size (mm)	pcs/box	plane	shi
F	F0059400C	25	55	400x400x460	1	12	24
F	F0059413B	25	55	400x400x460	1	12	24
F	F0059414B	25	55	400x400x460	1	12	24

400x400x460

400x400x460



ship 24

24

24

24

24

12

12

Product Range - Technical Data Flow-Rate Voltage Hose Filter H2O Fluid Pump Meter Nozzle Inlet РС Users Code Description Туре Mod. Mod connection No. AC. V/Hz DC Volt Power Watt l/min Length Ø gpm D NO 1" F0059400C Cube 70 MC 70 18 230/50 900 4.2 Panth 72 K600 Auto 4m Yes 50 F0059413B Cube 70 MC DC 12V D 56 15 12 300 35 Panth DC K600 Auto NO 4m 1" Yes 50 F0059414B Cube 70 MC DC 24V D Panth DC NO 1" 70 18 24 420 25 K600 Auto 4m Yes 50 F0059415B Cube 70 MC 120 UT D 230/50 NO 1" 1" 70 18 550 3.2 Panth 72 K600 Auto Yes 120 F00594220 Cube 70 MC 12V 120 UT D Panth DC 1" 56 15 12 300 35 K600 NO 120 Auto Yes

1

1

11 Camomile Way, Bibra Lake W.A, 6163

F0059415B

F00594220

Phone: (08) 6166 3860

E-mail: admin@rtrswa.com.au

